



Opus 800

PRODUCT OPTIONS AND ACCESSORIES

- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- OA8950/C Lincat Opus 800 Free-standing Floor Stand with Castors - for units W 600 mm
- OA8950 Lincat Opus 800 Free-standing Floor Stand with Legs - for units W 600 mm
- RC03M RADIANT COVER - OPUS 800

PRODUCT FEATURES

- Three heat zones which are capable of maintaining different temperatures on the same surface, allowing you to cook chicken fillets only inches away from steaks. Individual zones can be turned off during quiet periods.
- Highly powerful infra-red burners respond quicker and heat faster than standard burners allowing you to increase your output and achieve energy savings
- Heavy-duty cast iron branding grids with reversible design, for uninterrupted cooking and self cleaning at maximum power
- Flame failure protection
- Heavy duty radiant caps protect burners

Embrace the unique power and versatility of the Opus 800 Three-Zone Gas Chargrill, which provides three heat zones which are capable of maintaining different temperatures on the same surface, allowing you to cook chicken fillets only inches away from steaks. Highly powerful infrared burners respond quicker and heat faster than standard burners, allowing you to increase your output and achieve energy savings at the same time. Perfect for any busy commercial kitchen, the chargrill comes with heavy-duty cast iron branding grids with a reversible design for uninterrupted cooking and self cleaning at maximum power. There's also flame failure protection for added safety.

A/A FILE NUMBER:

ITEM NUMBER:



LINCAT OPUS NATURAL GAS COUNTER-TOP CHARGRILL - W 600 MM - 13.8 KW

MODEL: OG8401/N

WEIGHTS & DIMENSIONS

Width	600 mm
Depth	806 mil
Height	653 mm
Weight	80.5 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	806 cm
Ship Height	79 cm
Ship Weight	88.55 kg
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Gas	Gas Inlet Size	0.5 in
Electrical Kilowatts	13.8 kW	Gas Inlet Pressure Required	20 mBar
Dedicated Circuit Required	Yes	Gas Consumption at Max Use Per Hour	1.24 m ³
Gas Type	Natural Gas	Total Heat Input at Max Use	13.8 kW, 47087 BTU per hour
Gas Total BTUs	47086 BTU		

ADDITIONAL SPECIFICATIONS

Base Type	Not Applicable	Grate Type	Cast Iron
Burner Material	Stainless Steel	Ignition Type	Pilot Light
Charbroiler Type	Countertop	Number of Burners	3
Construction Materials	Stainless Steel	Number Of Controls	3
Control Type	Mechanical, Rotary Control Knob	Radiant Material	Ceramic Plaque
Cooking Area Plate Depth	620 mm	Ventless Cooking Technology	No
Cooking Area Plate Width	500 mm	Slide Out Warming Rack	No
Food Production Rate	78 x 225g [8oz] steaks [chilled] per hour	Towel Bar	No

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
March 25, 2025

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

