



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- SLS6V Lincat Silverlink 600 Free-standing Floor Stand - for V6 Series Ovens - W 600 mm
- V6/T V6 TOP COVER

PRODUCT FEATURES

- Excellent performance and optimum efficiency oven operating from a 13A plug
- Accommodates 2/3 gastronorms
- Four shelf positions with two removable shelves
- Able to support Silverlink 600 counter top units such as boiling tops, bains marie, griddles and work tops
- Stainless steel interior with radiused corners and removable side shelf supports for easy cleaning

Cook with confidence with the Silverlink 600 Electric Oven. Ideal for care homes as well as smaller pubs and restaurants, the oven, which accommodates 2/3 GN dishes, guarantees excellent performance and optimum efficiency operating from a 13A plug. Multi-use, there are four shelf positions with two removable shelves, while the oven is also able to support Silverlink 600 counter top units such as boiling tops, bains marie, griddles and work tops.

AIA FILE NUMBER:

ITEM NUMBER:



LINCAT SILVERLINK ELECTRIC FREE-STANDING OVEN - W 600 MM - 3.0 KW

MODEL: V6

WEIGHTS & DIMENSIONS

Width	600 mil
Depth	623 mil
Height	674 mil
Weight	45 kg

SHIPPING DETAILS

Ship Width	70.3 cm
Ship Depth	70.3 cm
Ship Height	102.3 cm
Ship Weight	49.5 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	13 A	Number of Electrical Plugs	1
Electrical Volts	240V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	3000 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	3 kW	Dedicated Circuit Required	No
Electrical Phase	1-Phase	Electrical Remarks	Single

ADDITIONAL SPECIFICATIONS

Construction Materials	Stainless Steel	Door Type	Solid
Control Type	Mechanical, Rotary Control Knob	Fan Assisted	No
Cooking Chamber Depth	335 mm	Gastronorm Capacity	1 x GN2/3
Cooking Chamber Height	420 mm	Number of Wire Racks	3
Cooking Chamber Width	470 mm	Ventless Cooking Technology	No
Cooking Rack Depth	335 mm	Temperature Maximum	250 °C
Cooking Rack Width	455 mm	Temperature Minimum	50 °C

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
March 25, 2025

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

