

THAWSAFE TECHNICAL DATASHEET

WTS75 THAWSAFE



WTS75

Dimensions (mm)	External	Internal
Width	727	567
Depth	941	807
Height	1960	1411
Door Opening		567

Capacity

Max load capacity (kg)	75
------------------------	----

KEY FEATURES

- Foodsafe stainless steel exterior and interior
- Easy to clean dished base with radiused corners
- Intuitive touchscreen controller with simple to operate icon based menu
- Designed and engineered to operate efficiently up to a 43°C ambient
- Self closing door
- Precision injected, high density 75mm polyurethane insulation
- Heavy duty, non-marking swivel castors with brakes
- Barrel locked door
- Product does not exceed 5°C throughout the thawing process
- Natural hydrocarbon refrigerant
- Fitted with 8 of 2/1 GN nylon coated wire shelves
- Anti-tilt trayslides
- Cooking thawed food is quicker and safer than cooking from frozen - eliminating the risk of cold spots once cooking has finished
- Designed with forced air heating and cooling circuits which cycle alternatively keeping the food within the correct temperature range of 0°C to +5°C
- Connection to third party supervisory communication systems such as BMS is possible using proprietary equipment. Please contact Williams for more information.

OPTIONS

- Stainless steel back



THAWSAFE TECHNICAL DATA

ThawSafe	WTS75
Temperature (°C)	0/+5
Power Supply	220V/240V 50Hz/1Ph
Fuse (Amps)	13
Defrost	Automatic off cycle
Noise Level (dBA)	59

Fittings	
2/1 GN Shelves (530 x 650mm)	8

Electrical Data - Standard Refrigerant	
Refrigerant	R290
Start Up (Amps)	6.8
Running (Amps)	6.8
Heat Rejection (kW / 24hrs)*	692

IMPORTANT NOTES:

*Heat rejection is evaporating at -10°C in 32°C Ambient	Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.
The WTS75 requires connection to a main drain	
All refrigeration equipment requires adequate ventilation for efficient and effective performance.	

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

