



*Opus* 800

#### PRODUCT OPTIONS AND ACCESSORIES

- OA8924 BASKET-PASTA BOILER - 143 x 288 x 230 DEEP
- OA8922 BASKET-PASTA BOILER - 298 x 328 x 230 DEEP
- OA8928 GASTRONORM & LID
- OA8925 PASTA BOILER BASKET 1/6 SQUARE - 143 x 163 x 230 DEEP

#### PRODUCT FEATURES

- Flexible - can be used as a pasta boiler, steamer or bain marie, saving valuable space
- Two position water setting: fast fill, or trickle fill for maintaining water level while cooking
- Direct connection to water supply and waste
- Starch removal system keeps water fresh
- Boil dry protection
- GN1/1 compatible

If you're looking for a pasta boiler, steamer and Bain Marie but don't have the space for all of these appliances, then you'll love the Opus 800 Electric Pasta Boiler, which can do all of these things. Whether you're cooking in a large pub or a restaurant, save valuable space with the flexible pasta boiler that's also a steamer and a Bain Marie. With direct connection to the water supply and waste, the boiler comes with a starch removal system to keep water fresh, as well as boil dry protection. Then there's the two position water setting, which allows for a fast fill or a trickle fill to maintain the water level while cooking.

**WEIGHTS & DIMENSIONS**

Width	400 mil
Depth	800 mil
Height	1020 mil
Weight	58.4 kg

**SHIPPING DETAILS**

Ship Width	85 cm
Ship Depth	45 cm
Ship Height	122 cm
Ship Weight	64.24 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

**WATER, PLUMBING, AND DRAINAGE SPECS**

Water Line Required	Yes
Water Connection Source Type	Water Main
Water Inlet Size	0.75 in
Water Inlet Pressure Minimum	0.2 Bar
Water Inlet Pressure Maximum	10 Bar
Drain Line Required	Yes
Drain Outlet Size	28 mm

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Type	Electric
Electrical Amps Per Conductor	Single Phase 26.1/Three Phase L1=13.0; L2=13.0; L3=N/
Electrical Total Amperage	26.1 A
Electrical Volts	230-400V
Electrical Total Wattage	6000 W
Electrical Kilowatts	6 kW

Electrical Plug Type	Hardwired
Number of Electrical Plugs	Not Applicable
Electrical Connection Type	Direct Hardwired
Number of Electrical Conductor Wires	1
Dedicated Circuit Required	Yes
Electrical Remarks	Single, Three



**ADDITIONAL SPECIFICATIONS**

Capacity (Volume)	24 l	Overflow Prevention	Yes
Construction Materials	Stainless Steel	Ventless Cooking Technology	No
Control Type	Mechanical	Temperature Maximum	190 °C
Mixing Valve	No	Temperature Minimum	130 °C
Number of Baskets	0	Water Fill	Automatic
Number of Vats (batteries)	1		

**BIDDING SPECIFICATIONS (SHORT FORM SPECS)**

Bidding Specifications Not Available.

TECHNICAL DRAWING

