



SILVERLINK 600

The Silverlink 600 Electric Chargrill allows you to create that distinctive chargrilled flavour and fire branded appearance without the mess. The water bath keeps food succulent and reduces shrinkage, while the high heat retention cast iron grids ensure your output stays high throughout cooking - there's no need to wait for the grill to recover to cooking temperature. It's perfect for cafes, bars and restaurants.

A/A FILE NUMBER:

PRODUCT OPTIONS AND ACCESSORIES

- CC6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm
- CN6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
- SLS6 Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm
- HC6 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW
- HCL6 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW

PRODUCT FEATURES

- Offers the authentic taste and branded appearance of chargrilled food without the need for lava rock
- High heat retention of cast iron grids means there is no waiting for the grill to recover to cooking temperature
- The water bath keeps food succulent and reduces shrinkage, while the high heat retention cast iron grids ensure your output stays high throughout operation
- Hinging interlocked elements and integral water bath makes cleaning easier
- Integral splashguard with water funnel enables refilling of tank without cooling the cooking grid
- High temperature safety cut out for protection if water bath runs dry

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Width	600 mil
Depth	620 mil
Height	385 mil
Weight	29.8 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	70 cm
Ship Height	59.5 cm
Ship Weight	32.78 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	Hardwired
Electrical Amps Per Conductor	Single Phase 34.8/Three Phase L1=11.6; L2=11.6; L3=11.6	Number of Electrical Plugs	Not Applicable
Electrical Total Amperage	34.8 A	Electrical Connection Type	Direct Hardwired
Electrical Volts	230-400V	Number of Electrical Conductor Wires	1
Electrical Total Wattage	8000 W	Dedicated Circuit Required	Yes
Electrical Kilowatts	8 kW	Electrical Remarks	Single,Three

ADDITIONAL SPECIFICATIONS

Construction Materials	Stainless Steel	Grate Type	Cast Iron
Control Type	Mechanical, Rotary Control Knob	Number Of Controls	1
Cooking Area Plate Depth	400 mm	Number of Heating Elements	1
Cooking Area Plate Width	470 mm	Number of Heating Zones	1
		Ventless Cooking Technology	No

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

