



SEAL

PRODUCT FEATURES

- Stylish, rounded and compact design for attractive display where space is at a premium
- Minimum food holding temperature of 72°C
- Thermostatic control up to 95°C
- Robust stainless steel construction - hygienic and easy to clean
- Four chrome-plated rod shelves with easy to remove supports for effortless cleaning

Attract customers while providing an economical solution to displaying pies and pastries with the Seal Pie Cabinet. Ideal for fish and chip shops, fast food outlets, cafes and canteens, its stylish, rounded and compact design makes for an attractive display where space is at a premium, while its built-in humidity feature prevents food from drying out, keeping it in optimum condition for longer. With a minimum food holding temperature of 72°C and thermostatic control up to 95°C, the cabinet's robust stainless steel construction means it's both hygienic and easy to clean.



LINCAT SEAL COUNTER-TOP PIE CABINET WITH ILLUMINATION AND HUMIDITY FEATURE - HEATED - W 710 MM - 0.8 KW

MODEL: LPW/LR

WEIGHTS & DIMENSIONS

Width	710 mil
Depth	330 mil
Height	520 mil
Weight	29.7 kg

SHIPPING DETAILS

Ship Width	81 cm
Ship Depth	43 cm
Ship Height	60 cm
Ship Weight	32.67 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	3.5 A	Number of Electrical Plugs	1
Electrical Volts	230V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	800 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	0.8 kW	Dedicated Circuit Required	No
Electrical Phase	1-Phase	Electrical Remarks	Single

ADDITIONAL SPECIFICATIONS

Construction Materials	Stainless Steel	Shelf Depth	275 mm
Control Type	Mechanical	Shelf Width	605 mm
Display Case Service Type	Front of House Service	Type of Lighting	Fluorescent
Heated Base	Yes	Temperature Maximum	95 °C
Number of Shelves	4	Temperature Minimum	72 °C
Rack Type	Static		

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

