



Opus 800

PRODUCT OPTIONS AND ACCESSORIES

- LK02 OPUS 350 LEG KIT
- OA8954 SPLASHGUARD FOR OPUS 800 ELECTRIC FRYERS

PRODUCT FEATURES

- Two independent fryer tanks for greater versatility
- Accurate thermostatic control up to 190°C for consistent results and safe operation
- Pumped oil return enables the oil to be filtered and the fryer ready for use again in less than five minutes - safe and convenient
- Oil can be filtered during or after service even whilst hot
- Hinged, lift out element, with safety interlock for easy tank access and cleaning

Fry delicious food accurately with this Opus 800 Twin-Tank Free Standing Electric Fryer which comes with two independent fryer tanks for greater versatility. The fryer boasts a pumped oil system which allows the oil to be filtered and ready to use again in less than five minutes. The two-stage filtration system not only extends oil life by up to 75%, but also saves you money. With a precise thermostatic control, the fryer is ideal for a variety of busy commercial kitchens, whether it's a large pub or a restaurant. The hinged, lift out element with safety interlock makes it easy to access and clean the tank.



LINCAT OPUS ELECTRIC FREE-STANDING TWIN TANK FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 600 MM - 24.0 KW

MODEL: OE8113/OP

WEIGHTS & DIMENSIONS

Width	600 mil
Depth	800 mil
Height	1070 mil
Weight	104 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	85 cm
Ship Height	122 cm
Ship Weight	114.4 kg
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Phase	3-Phase
Electrical Amps Per Conductor	L1/L2/L3= 34.8 [1 cab]; L1/L2/L3= 2 x 17.4 [2 cab]	Electrical Plug Type	Hardwired
Electrical Total Amperage	34.8 A	Number of Electrical Plugs	Not Applicable
Electrical Volts	400V	Electrical Connection Type	Direct Hardwired
Electrical Total Wattage	24000 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	24 kW	Dedicated Circuit Required	Yes
		Electrical Remarks	Three

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
March 24, 2025



LINCAT OPUS ELECTRIC FREE-STANDING TWIN TANK FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 600 MM - 24.0 KW

MODEL: OE8113/OP

ADDITIONAL SPECIFICATIONS

Auto Oil Top-Off	No	Number of Baskets	2
Basket Lift Type	Not Applicable	Number of Vats (batteries)	2
Construction Materials	Stainless Steel	Total Oil Capacity (volume)	30 l
Control Type	Mechanical	Oil Reclamation	No
Filter Media Type (if applicable)	2-Stage: Fine Tissue Filter and Stainless Steel Filter	Oil Temperature Control	Mechanical
Food Production Rate	64kg chips - 12mm [frozen], 84kg chips - 12mm [chilled] per hour	Pumped Oil Filtration	Yes
Fryer Type	Open Pot	Vat 1 Oil Capacity (volume)	15 l
Integrated Filtration	Yes	Vat 2 Oil Capacity (volume)	15 l
		Ventless Cooking Technology	No
		Split Pot	Yes
		Temperature Maximum	190 °C

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

